



Rely on it.

### Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



## RENOLIT ALKORPLUS PRIMER 81802 POLIQUID

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** RENOLIT ALKORPLUS  
PRIMER  
81802 POLIQUID

**Other means of identification:**

Non-applicable

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Primer for impermeabilizing coverings. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

RENOLIT IBERICA SA  
Ctra. del Montnegre, s/n  
08470 Sant Celoni - Barcelona - España  
Phone: +34 938484000 - Fax: +34 938675936  
renolit.iberica@renolit.com  
http://www.renolit.com/

**1.4 Emergency telephone number:** +44 1235 239 670

### SECTION 2: HAZARDS IDENTIFICATION

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319  
Flam. Liq. 2: Flammable liquids, Category 2, H225  
Skin Irrit. 2: Skin irritation, Category 2, H315  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

Danger



**Hazard statements:**

Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
STOT SE 3: H335 - May cause respiratory irritation.

**Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261: Avoid breathing vapours.  
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P312: Call a POISON CENTER/doctor if you feel unwell.  
P403+P233: Store in a well-ventilated place. Keep container tightly closed.

**Supplementary information:**

Contains 2-ethylhexyl acrylate, Methyl methacrylate, Neopentyl glycol propoxylate diacrylate, reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ).

**UFI:** R110-Y0JQ-5002-R7N2

**2.3 Other hazards:**

- CONTINUED ON NEXT PAGE -

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 1/13



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



**RENOLIT ALKORPLUS  
PRIMER  
81802 POLIQUID**

Date of compilation: 22/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

Product fails to meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product fails to meet the criteria.  
This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).  
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**  
Non-applicable

**3.2 Mixture:**  
**Chemical description:** Mixture of substances  
**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 80-62-6 EC: 201-297-1 Index: 607-035-00-6 REACH: 01-2119452498-28-XXXX	Methyl methacrylate <sup>□1□</sup>	ATP CLP00	25 - <50 %
	Regulation 1272/2008	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	
CAS: 25068-38-6 EC: 500-033-5 Index: 603-074-00-8 REACH: Non-applicable	reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ) <sup>□1□</sup>	Self-classified	25 - <50 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	
CAS: 103-11-7 EC: 203-080-7 Index: 607-107-00-7 REACH: 01-2119953158-37-XXXX	2-ethylhexyl acrylate <sup>□1□</sup>	ATP CLP00	2,5 - <10 %
	Regulation 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	
CAS: 84170-74-1 EC: 617-546-6 Index: Non-applicable REACH: 01-2119970213-43-XXXX	Neopentyl glycol propoxyate diacrylate <sup>□2□</sup>	Self-classified	0,25 - <1 %
	Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Sens. 1A: H317 - Warning	

<sup>□1□</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878  
<sup>□2□</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



### RENOLIT ALKORPLUS PRIMER 81802 POLIQUID

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

#### SECTION 4: FIRST AID MEASURES (continued)

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

#### SECTION 5: FIREFIGHTING MEASURES

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

- CONTINUED ON NEXT PAGE -

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 3/13



**RENOLIT ALKORPLUS  
PRIMER  
81802 POLIQUID**

Date of compilation: 22/07/2020      Revised: 05/08/2022      Version: 3 (Replaced 2)

**SECTION 7: HANDLING AND STORAGE (continued)**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.:            5 °C  
Maximum time:            36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Methyl methacrylate CAS: 80-62-6    EC: 201-297-1	IOELV (8h)	50 ppm	
	IOELV (STEL)	100 ppm	

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	13,67 mg/kg	Non-applicable
	Inhalation	Non-applicable	416 mg/m <sup>3</sup>	348,4 mg/m <sup>3</sup>	208 mg/m <sup>3</sup>
reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ) CAS: 25068-38-6 EC: 500-033-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,75 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4,93 mg/m <sup>3</sup>	Non-applicable
2-ethylhexyl acrylate CAS: 103-11-7 EC: 203-080-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	6,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	38 mg/m <sup>3</sup>	Non-applicable	38 mg/m <sup>3</sup>

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS  
PRIMER  
81802 POLIQUID**

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Neopentyl glycol propoxylate diacrylate CAS: 84170-74-1 EC: 617-546-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	46,7 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32,9 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable
	Inhalation	Non-applicable	208 mg/m <sup>3</sup>	74,3 mg/m <sup>3</sup>	104 mg/m <sup>3</sup>
reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ) CAS: 25068-38-6 EC: 500-033-5	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,0893 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,87 mg/m <sup>3</sup>	Non-applicable
2-ethylhexyl acrylate CAS: 103-11-7 EC: 203-080-7	Oral	Non-applicable	Non-applicable	0,23 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,34 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	4,5 mg/m <sup>3</sup>

**PNEC:**



Identification				
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	STP	10 mg/L	Fresh water	0,94 mg/L
	Soil	1,48 mg/kg	Marine water	0,094 mg/L
	Intermittent	0,94 mg/L	Sediment (Fresh water)	10,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,102 mg/kg
reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ) CAS: 25068-38-6 EC: 500-033-5	STP	10 mg/L	Fresh water	0,006 mg/L
	Soil	0,065 mg/kg	Marine water	0,001 mg/L
	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,341 mg/kg
	Oral	0,011 g/kg	Sediment (Marine water)	0,034 mg/kg
2-ethylhexyl acrylate CAS: 103-11-7 EC: 203-080-7	STP	2,3 mg/L	Fresh water	0,00272 mg/L
	Soil	1 mg/kg	Marine water	0,000272 mg/L
	Intermittent	0,011 mg/L	Sediment (Fresh water)	0,108 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0108 mg/kg
Neopentyl glycol propoxylate diacrylate CAS: 84170-74-1 EC: 617-546-6	STP	0,1 mg/L	Fresh water	0,003 mg/L
	Soil	0,011 mg/kg	Marine water	0 mg/L
	Intermittent	0,027 mg/L	Sediment (Fresh water)	0,064 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,006 mg/kg

**8.2 Exposure controls:**

**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

- CONTINUED ON NEXT PAGE -



Rely on it.

### Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



## RENOLIT ALKORPLUS PRIMER 81802 POLIQUID



Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



#### D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

#### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

#### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0 % weight
V.O.C. density at 20 °C:	0 kg/m <sup>3</sup> (0 g/L)
Average carbon number:	Non-applicable
Average molecular weight:	Non-applicable

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C: Liquid

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 6/13



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



**RENOLIT ALKORPLUS  
PRIMER  
81802 POLIQUID**

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Appearance:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	101 °C
Vapour pressure at 20 °C:	3870 Pa
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	1030 kg/m <sup>3</sup>
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	600 cP
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Immiscible
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

**Flammability:**

Flash Point:	22 °C (ISO 3680)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	430 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**Particle characteristics:**

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

**Other safety characteristics:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Rely on it.

### Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



## RENOLIT ALKORPLUS PRIMER 81802 POLIQUID

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

Contains substances highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

##### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

##### A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

##### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

##### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Methyl methacrylate (3); 2-ethylhexyl acrylate (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

- CONTINUED ON NEXT PAGE -

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 8/13





Rely on it.

### Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



## RENOLIT ALKORPLUS PRIMER 81802 POLIQUID

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

#### F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

#### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Non-applicable

#### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
2-ethylhexyl acrylate	4435 mg/kg	7552 mg/kg	Rat
CAS: 103-11-7			Rabbit
EC: 203-080-7	LC50 inhalation	Non-applicable	

#### 11.2 Information on other hazards:

##### Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

##### Other information

Non-applicable

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.1 Toxicity:

##### Acute toxicity:

- CONTINUED ON NEXT PAGE -

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 9/13



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



**RENOLIT ALKORPLUS  
PRIMER  
81802 POLIQUID**

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration	Species	Genus
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	LC50 191 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50 69 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 170 mg/L (96 h)	Selenastrum capricornutum	Algae
Neopentyl glycol propoxylate diacrylate CAS: 84170-74-1 EC: 617-546-6	LC50 2,7 mg/L (96 h)	Danio rerio	Fish
	EC50 37 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 3,4 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

**Chronic toxicity:**

Identification	Concentration	Species	Genus
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	NOEC 9,4 mg/L	Danio rerio	Fish
	NOEC 37 mg/L	Daphnia magna	Crustacean
reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ) CAS: 25068-38-6 EC: 500-033-5	NOEC Non-applicable		
	NOEC 0,3 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94,3 %
reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ) CAS: 25068-38-6 EC: 500-033-5	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
Neopentyl glycol propoxylate diacrylate CAS: 84170-74-1 EC: 617-546-6	BOD5	Non-applicable	Concentration	2 mg/L
	COD	Non-applicable	Period	56 days
	BOD5/COD	Non-applicable	% Biodegradable	70 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	BCF	7
	Pow Log	1.38
	Potential	Low
reaction product: bisphenol-A-(epichlorhydrin) ( 700 < MW < 1100 ) CAS: 25068-38-6 EC: 500-033-5	BCF	4
	Pow Log	2.8
	Potential	Low

- CONTINUED ON NEXT PAGE -



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS PRIMER 81802 POLIQUID

Date of compilation: 22/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.4 Mobility in soil:

Table with 3 main columns: Identification, Absorption/desorption, and Volatility. Rows include Methyl methacrylate and 2-ethylhexyl acrylate with their respective properties.

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Table with 3 columns: Code, Description, and Waste class (Regulation (EU) No 1357/2014). Row: 08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances, Dangerous.

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

- CONTINUED ON NEXT PAGE -



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS PRIMER 81802 POLIQUID

Date of compilation: 22/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 14: TRANSPORT INFORMATION (continued)

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: I
14.5 Marine pollutant: No
14.6 Special precautions for user
Special regulations: 367, 163
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 500 mL
Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: I
14.5 Environmental hazards: No
14.6 Special precautions for user
Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Table with 4 columns: Section, Description, Lower-tier requirements, Upper-tier requirements. Row 1: P5c, FLAMMABLE LIQUIDS, 5000, 50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....)

Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

- CONTINUED ON NEXT PAGE -



Rely on it.

### Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



## RENOLIT ALKORPLUS PRIMER 81802 POLIQUID

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

### SECTION 15: REGULATORY INFORMATION (continued)

#### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

#### Texts of the legislative phrases mentioned in section 2:

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Date of compilation: 22/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 13/13

Document generated with Chemeter ([www.siam-it.com](http://www.siam-it.com))