


# RENOLIT ALKORPLAN L

## Loose laid & ballasted system



SQUAD.BE

### Product information

**RENOLIT ALKORPLAN L**  
Synthetic roofing membrane of flexible PVC, reinforced with a glass fleece.

### Application

RENOLIT ALKORPLAN L is used as waterproofing membrane within loose laid systems, protected with gravel or tiles on tile supports.

### Certificates

Product certification EN 13956  
0749-CPR / BC2-320-01452-0001-01

Certificates available on our website  
[www.renolit.com/roofing](http://www.renolit.com/roofing).

PRODUCT DATA			
	Method	Production values RENOLIT ALKORPLAN L	Unit
		1,5 mm	
Tensile strength	EN 12311-2 (B)	≥9	N/mm <sup>2</sup>
Elongation at break	EN 12311-2 (B)	≥180	%
Dimensional stability (6 h at 80 °C)	EN 1107-2	≤0,1	%
Foldability at low temperature	EN 495-5	≤-25	°C
Nail tear resistance	EN 12310-1	≥325	N
Tear resistance	EN 12310-2	≥120	N
Joint peel resistance	EN 12316-2	≥ B0J eller 200	N/50 mm
Water vapour diffusion resistance (μ)	EN 1931	20 000	-
Resistance to static perforation	EN 12730	≥20	kg

PACKAGING						
	Colour	Thickness	Width	Weight	Roll length	Roll weight
RENOLIT ALKORPLAN L <sub>35177</sub>	Charcoal/Light Grey	1,5 mm	2,15 m	1,80 kg/m <sup>2</sup>	10 lm	ca. 40 kg
	Light Grey	1,5 mm	2,15 m	1,80 kg/m <sup>2</sup>	20 lm	ca. 80 kg

### Storage

The rolls should be stored horizontally and parallel to each other. Store in the original packaging, in a dry and frost-free area, protected from direct sunlight. The maximum stack height is 3 high with a protection between the pallets.

RENOLIT ALKORPLAN roofing membranes are supplied in rolls on cardboard cores. Every delivery may contain up to 10% of short rolls (minimum length: 8 m).

*This document replaces and supersedes all prior versions.*

**WWW.RENOLIT.COM/ROOFING**

RENOLIT Nordic A/S - Naverland 31 - 2600 Glostrup - Danmark  
T +45 43 64 46 33 - [renolit.nordic@renolit.com](mailto:renolit.nordic@renolit.com)



R2077ES0821