

Attractive  
windows are  
a pleasure.



RENOLIT EXOFOL Films.  
Cleaning made simple.





*Rely on it.*

## When something accidentally spills during installation.

Wherever there is construction, there is dirt, and a splash of plaster or paint can easily land on that brand new window frame. Care should be taken when cleaning **RENOLIT EXOFOL** films, as abrasive or corrosive products such as scouring agents, solvents or sharp-edged tools can cause permanent damage.


Hot tap water and ordinary washing-up liquid are sufficient to remove tile adhesive, paint or plaster residues. In these cases, use plenty of water and be patient. Soak the dirt thoroughly then rinse away the loosened particles, otherwise it acts like sandpaper.



## For the annual spring clean.

With RENOLIT EXOFOL films, having clean window frames is a foregone conclusion, because dirt particles have difficulty sticking to their surface.

Regular household cleaning is easy. Hot tap water, a soft brush or sponge and a squirt of washing-up liquid are all that is needed to remove summer dust or winter dirt. Under no circumstances should you scrub or rub, otherwise the top layer of the film will be damaged and its protective effect impaired.



## RENOLIT SE

Market Unit Exterior Solutions

Horchheimer Str. 50

67547 Worms | Germany

Phone: +49.6241.303.1040

Fax: +49.6241.303.18.1139

## RENOLIT UK Limited

Station Road

Northumberland, NE23 8AQ

Cramlington | United Kingdom

Phone: +44.1670.718222

Fax: +44.1670.590096

[exteriorsolutions@renolit.com](mailto:exteriorsolutions@renolit.com)  
[www.renolit.com/exteriorsolutions](http://www.renolit.com/exteriorsolutions)

vinyl<sup>plus</sup>



*Rely on it.*