

Innovation
and design
combined.


RENOLIT GEOFOL FH
Guyana Teak
9.3241 802

RENOLIT GEOFOL FH.
For lamination to exterior flooring
and decking.




Rely on it.





RENOLIT GEOFOL FH
Cayenne Oak
3.0078 016

Range at a glance.



RENOLIT GEOFOL FH
AnTEAK
9.3241 804




RENOLIT GEOFOL FH
Coriander Oak
3.0078 013



RENOLIT GEOFOL FH
Mountain Oak
2.0057 008




RENOLIT GEOFOL FH
Honey Oak
3.0078 018




RENOLIT GEOFOL FH
Cumin Oak
3.0078 019



RENOLIT GEOFOL FH
Nutmeg Oak
3.0078 020



RENOLIT GEOFOL FH
Macore
9.3162 803



RENOLIT GEOFOL FH
Urban Spirit 1
2.0089 007

Tread new paths.

With RENOLIT GEOFOL FH you can make decking or balcony floor boards look great. Whether made of aluminium, PVC or other plastics, the film gives every board a natural look with its range of high quality designs. Household washing-up liquid, lukewarm water, and a soft brush or soft sponge are all that is needed for cleaning. The top layer contains corundum which provides the necessary slip resistance. RENOLIT GEOFOL FH is extremely scratch and abrasion resistant as well as resistant to substances such as ketchup, red wine and cooking oil.

Take advantage of our experience.

With RENOLIT GEOFOL FH, you are breaking new ground in the design of flooring boards and decking but at the same time benefiting from our decades of experience working with lamination films. RENOLIT GEOFOL FH can be applied without any problems using established methods and adhesive systems. Our beautiful decors remain reliably stable, and our Solar Shield Technology (SST) protects the film and board from excessive heat.

Strong benefits in every aspect.




Tread resistance protected by scratch and abrasion resistant surface




Resistant to mould and algae



Suitable for bare feet due to pleasant temperature and soft feel



SST reduces heat build-up




Scratch resistant surface



Impact resistant surface



Highly slip resistant



Protected against weather and UV radiation

RENOLIT SE

Market Unit Exterior Solutions

Horchheimer Str. 50

67547 Worms | Germany

Phone: +49.6241.303.1040

Fax: +49.6241.303.18.1139

RENOLIT UK Limited

Station Road

Northumberland, NE23 8AQ

Cramlington | United Kingdom

Phone: +44.1670.718222

Fax: +44.1670.590096

exteriorsolutions@renolit.com
www.renolit.com/exteriorsolutions

vinyl^{plus}



Rely on it.