

RENOLIT BENDIT.
For that certain bend.



RENOLIT BENDIT combines.

RENOLIT BENDIT is an edging sheet that can be used to create panelling around a PVC-U window. Its surface consists of a surface coating film specially developed for this purpose. It is available in a selection of colours, designs and surface textures and features all the renowned strengths of RENOLIT EXOFOL, such as easy cleaning and Solar Shield Technology (SST).

With RENOLIT BENDIT, you can create seamless pillar and corner coverings, reveal and lintel panelling and many other solutions that look as if they have been cast from a single mould: with a visually seamless transition to the window profile or deliberately contrasting with the fabric of the building.

RENOLIT BENDIT product properties.



Exceptional thermal stability



Sustainable and durable



Appearance and texture like window film



High bending stability



UV and weather resistant



Universal application



Light weight




Flat panel surface

You can bend RENOLIT BENDIT

Schematic structure RENOLIT BENDIT

Panel size: 1.250 x 2.800 x 4,2 mm



Processing the high-quality cladding panel is extremely simple: mill a small groove into the back of the panel and you can bend RENOLIT BENDIT to the exact angle you need. Any angle up to 90 degrees is possible. The fold is positioned exactly where you want it, and the beautiful surface can withstand it all.



Further information can be found at www.renolit.com/bendit

RENOLIT SE

Market Unit Exterior Solutions Horchheimer Str. 50 67547 Worms | Germany Phone: +49.6241.303.1040 Fax: +49.6241.303.18.1139

RENOLIT UK Limited

Station Road Northumberland, NE23 8AQ Cramlington | United Kingdom Phone: +44.1670.718222 Fax: +44.1670.590096

exteriorsolutions@renolit.com www.renolit.com/exteriorsolutions



